


488

Premium Aluminum Foil Tape 25/50 Rated



Description: 488 is an aluminum foil with a pressure sensitive adhesive and flat paper liner.

Uses: This product is used with fiberglass duct-board on all seams and joints. It provides a dependable vapor barrier when applied to clean, dry surfaces. For best results, use of the plastic applicator is recommended. Store in a cool, dry place (60°F to 80°F).

Features / Benefits:

Dead Soft Aluminum Foil: Conforms to irregular surfaces such as FSK facings and blends with the basic facing pattern. Foil as a vapor barrier assures integrity of the insulation system.

Easily Removable Liner: Saves labor, materials and money at the time of application with consistent, predictable performance as liner is removed for the final tape application.

Special Adhesive: An aggressive adhesive once applied, assures durable performance.

Physical Properties*:	Adhesion to Backing	36 oz./in. width
	Adhesion to Steel	75 oz./in. width
	Adhesive	Rubber
	Backing	2 Mil Dead Soft Aluminum Foil
	Elongation	11%
	Tensile Break	23 lbs./in. width
	Temperature Range	-20°F - +150°F

Packaging:	Length	150 feet		
	Width	2 in.	2 1/2 in.	3 in.
	Rolls Per Case	24	20	16

*Pressure Sensitive Tape Council test methods used where applicable. Tests represent typical performance values. Specific values on request.

The Ideal Tape Company

1400 Middlesex St. TEL: 508-458-6833
Lowell, MA 01851 FAX: 508-458-0302

